

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 58

Revision: 02.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: MOTIP IMPREGNATION SPRAY

· Article number: 090104

 \cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

 $\cdot \textit{Application of the substance / the mixture Preparation}$

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com

• Further information obtainable from: QHSE Department • 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2H315Causes skin irritation.Eye Irrit. 2H319Causes serious eye irritation.STOT SE 3H336May cause drowsiness or dizziness.Classification according to Directive 67/548/EEC or Directive 1999/45/EC

F+; Extremely flammable R12: Extremely flammable.

2: Extremely flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

⁽Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 58

Revision: 02.06.2015

Trade name: MOTIP IMPREGNATION SPRAY

	r repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. ! Pressurised container.
	rcotising effect.
	ation system:
	ification is according to the latest editions of the EU-lists, and extended by company and literature
data.	
2 2 I ahe	l elements
	g according to Regulation (EC) No 1272/2008
	uct is classified and labelled according to the CLP regulation.
	nictograms
~	
JHL	
(23)	
\sim	\vee \vee
GHS02	GHS07 GHS09
a • 1	
Signal w	ord Danger
	letermining components of labelling:
Naphtha	(petroleum), hydrotreated light
propan-2	
n-butyl a	cetate
Hazard s	tatements
H222-H2	229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	<i>Toxic to aquatic life with long lasting effects.</i>
Precauti	onary statements
P102	Keep out of reach of children.
P260	Do not breathe spray.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking,
P251	Do not pierce or burn, even after use.
P211	Do not spray on an open flame or other ignition source.
P410+P4	412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local regulations.
Addition	al information:
EUH066	Repeated exposure may cause skin dryness or cracking.
2.3 Other	r hazards
Results of	f PBT and vPvB assessment
PBT: No	t applicable.
vPvB: No	ot applicable.
OT TO OTT	ON 3: Composition/information on ingredients

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

(Contd. on page 3) GB Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 58

Revision: 02.06.2015

Trade name: MOTIP IMPREGNATION SPRAY

CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	Contd. of page 2 50-75%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Xn R65	-
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane F + R12 Flam. Gas 1, H220	-
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Xi R36 F R11 R67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	-
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane F + R12 Flam. Gas 1, H220	- 5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane F+R12 Flam. Gas 1, H220 Press. Gas C, H280	- 5-10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate R10-66-67 Image: Flam. Liq. 3, H226 STOT SE 3, H336	- 2.5-5%

• Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

Page 4/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 58

Revision: 02.06.2015

Trade name: MOTIP IMPREGNATION SPRAY

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources.
 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

• *Information about fire - and explosion protection:* Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

 \cdot Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

• Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

(Contd. of page 3)

GB

Page 5/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 58

Revision: 02.06.2015

(Contd. of page 4)

Trade name: MOTIP IMPREGNATION SPRAY

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.

· Respiratory protection: Not required.

• Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves Not required.
- · Penetration time of glove material Not required.
- Eye protection: Not required.

SECTION 9: Physical and chemical properties

General Information Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	$< 0 \ ^{\circ}C \ (< 32 \ ^{\circ}F)$
	Not applicable, as aerosol.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	> 200 °C (> 392 °F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	12.0 Vol %
Vapour pressure at 20 $\cdot C$ (68 $\cdot F$):	3500 hPa (2625 mm Hg)
Density at 20 °C (68 °F):	0.668 g/cm ³ (5.574 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	r): Not determined.
	(Contd. on page

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 58

Revision: 02.06.2015

Trade name: MOTIP IMPREGNATION SPRAY

	(Contd. of page 5
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
 Solvent content: Organic solvents: EU-VOC: EU-VOC in %: 	98.7 % 659.6 g/l 98.75 %
 Solids content: 9.2 Other information 	1.3 % No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· Acute toxicity

64742-49-	0 Naphtha (p	etroleum), hydrotreated light
Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>193 mg/m3 (rat)
	LC50 / 4h	25.2 mg/l (rat)
	LC50 / 96 h	11.4 mg/l (fish)
67-63-0 pr	opan-2-ol	
Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50 / 4 h	30 mg/m3 (rat)
106-97-8 b	outane	
Inhalative	LC50 / 4 h	658000 mg/m3 (rat)
123-86-4 n	i-butyl acetat	e
Oral	LD50	10770 mg/kg (rat)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21.0 mg/m3 (rat)
	ritant effect:	n No irritant effect.

· Respiratory or skin sensitisation No sensitising effects known.

(Contd. on page 7)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 58

Revision: 02.06.2015

Trade name: MOTIP IMPREGNATION SPRAY

(Contd. of page 6)

SECTION 12: Ecological information

• Aquatic toxicity:	
64742-49-0 Napht	tha (petroleum), hydrotreated light
EC50 / 48 h	3 mg/l (daphnia magna)
EC50 / 72 h	30-100 mg/l (algae)
LC50/96 h	93-117 mg/l (fish)
67-63-0 propan-2-	ol
EC50 / 48 h	13299 mg/l (daphnia magna)
LC50 / 96 h (dynai	mic) 4200 mg/l (fish)
123-86-4 n-butyl a	icetate
EC50 / 48 h	44 mg/l (daphnia magna)
EC50 / 96 h	320 mg/l (algae)
LC50 / 24 h	205 mg/l (daphnia magna)
LC50 / 96 h	18 mg/l (Pimephales promelas)
· 12.2 Persistence a	nd degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· Ecotoxical effects:

· Remark: Toxic for fish

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

• 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

14 06 03* other solvents and solvent mixtures

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Non contaminated packagings may be recycled.

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 58

Revision: 02.06.2015

Trade name: MOTIP IMPREGNATION SPRAY

	(Contd. of page
IMDG	AEROSOLS
·IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
*	
· Class	2 5F Gases.
· Label	2.1 2.1
· IMDG, IATA	······ ··· ···························
· Class	2.1
· Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
• EMS Number:	F- D , S - U
14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	
	Not applicable.
Transport/Additional information:	
ADR	
\cdot Limited quantities (LQ)	
\cdot Excepted quantities (EQ)	Code: E0
· Transport category	Not permitted as Excepted Quantity 2
• Transport category • Tunnel restriction code	2 D
	~
· IMDG Limited quantities (LO)	IL
· Limited quantities (LQ) · Excepted quantities (EQ)	IL Code: E0
Excepted quantities (EQ)	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

*

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 58

Revision: 02.06.2015

Trade name: MOTIP IMPREGNATION SPRAY

(Contd. of page 8)

SEC	TION 16: Other information
	nformation is based on our present knowledge. However, this shall not constitute a guarantee for any ic product features and shall not establish a legally valid contractual relationship.
Relev	ant phrases
	Extremely flammable gas.
	Highly flammable liquid and vapour.
	Flammable liquid and vapour.
	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
R10	Flammable.
R10 R11	
R11 R12	Highly flammable.
R12 R36	Extremely flammable.
R30 R38	Irritating to eyes.
	Irritating to skin. 2 Toxis to gaugitic congrigues, may agues long term advance effects in the gaugitic environment
R65 R65	3 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.
R65 R66	
R60 R67	Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
N07	vapours may cause arowsiness and alguness.
Depar Conta	"tment issuing MSDS: R&D legislation and regulatory advisor a ct: Mr. K. Smedeman
	viations and acronyms:
	èglement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the
Interna	tional Transport of Dangerous Goods by Rail)
	International Civil Aviation Organisation
	ccord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International ge of Dangerous Goods by Road)
	International Maritime Code for Dangerous Goods
	international Air Transport Association
	Globally Harmonised System of Classification and Labelling of Chemicals
	S: European Inventory of Existing Commercial Chemical Substances S: European List of Notified Chemical Substances
	hemical Abstracts Service (division of the American Chemical Society)
	Lethal concentration, 50 percent
	Lethal dose, 50 percent
	Gas 1: Flammable gases, Hazard Category 1 Aerosol 1: Flammable aerosols, Hazard Category 1
	Gas C: Gases under pressure: Compressed gas
Flam. I	.iq. 2: Flammable liquids, Hazard Category 2
	iq. 3: Flammable liquids, Hazard Category 3
VIII IVI	it. 2: Skin corrosion/irritation, Hazard Category 2 it. 2: Serious eye damage/eye irritation, Hazard Category 2
Eye Irri	E 5: Specific target organ toxicity - Single exposure, Hazara Category 5
Eye Irri STOT S Asp. To	E 3: Specific target organ toxicity - Single exposure, Hazard Category 3 x. 1: Aspiration hazard, Hazard Category 1
Eye Irri STOT S Asp. To Aquatic	